



TCM-HS610Q TCM-HS620Q TCM-HS630Q

Description:

With built-in 70V/100V transformer, HS series column speaker realizes a high- voltage, low-current mode, which makes longer distance transmission and parallel connection of multiple loudspeakers possible. It is designed for indoor / outdoor occasions such as station, park, school, square, military camp, industrial park, beach, etc.

Features:

- The cabinet is made of high-quality fiberboard and birch cold-pressed leather, which eliminates the resonance sound of the cabinet and is suitable for indoor/outdoor use;
- Producing clear, bright and thorough sound;
- Elegant outlook, High IP rating,
- High impedance 70-100V transformer input
- Water proof horn for outdoor

TCM-HS620Q

Directional Analog Horn Speaker

Specification	TCM-HS610Q	TCM-HS620Q	TCM-HS630Q
Rated Power at 100V	5/10W	7.5/15W	15/30W
Rated Power at 80V	2.5/5W	3.75/7.5W	7.5/15W
Sound Pressure Level (1W/1M)	94dB	95dB	96dB
Maximum Sound Pressure Level at 1m	106dB	107dB	108dB
Frequency Response	400Hz-8KHz	400Hz-5KHz	400Hz-7.5KHz
Dispersion Angel	230 degree		
Environmental type	Indoor/Outdoor applications		
Speaker Installation	Bracket mount		
Operating Temperature	-15 °C to +55 °C		
Cable Size	Wire: 0.5 - 2.5 mm2		
Material Color	ABS/White		
Dimensions	180 x 130 x 190 mm	222 x 162 x 232 mm	280 x 360 x 170 mm
Weight	1.15Kg	1.36Kg	2.2Kg
Application	Versatile for various PA .Emergency and BGM		



Distributed by